

## Correas Z

Recomendada para pendientes máximas del 20%

CORREA	H mm	B mm	C mm	e mm	c mm	d mm	Y'x mm	Y'y mm	S cm <sup>2</sup>	Peso Kg/m	Ixx cm <sup>4</sup>	Wxx cm <sup>3</sup>	ixx cm	Iyy cm <sup>4</sup>	Wyy cm <sup>3</sup>	iyy cm	Ixy cm <sup>4</sup>	Iξ cm <sup>4</sup>	Iμ cm <sup>4</sup>	φ 0°
*Z-100x2	100	44	50	2	18	18	51,54	47,32	4,32	3,39	67,22	13,04	3,95	24,79	5,24	2,40	-30,89	83,48	8,53	27°45'
Z-100x2,5	100	44	50	2,5	18	18	51,64	47,07	5,32	4,17	81,54	15,79	3,92	29,57	6,28	2,36	-37,17	100,91	10,20	27°31'
*Z-120x2	120	44	50	2	18	18	61,66	47,46	4,72	3,70	103,21	16,74	4,68	24,80	5,22	2,29	-37,74	119,15	9,67	21°58'
Z-120x2,5	120	44	50	2,5	18	18	61,76	47,22	5,82	4,56	125,54	20,33	4,61	29,58	6,27	2,25	-45,45	143,65	11,47	21°43'
*Z-140x2	140	66	76	2	21	15	70,88	70,60	5,99	4,70	189,94	26,80	5,63	71,05	9,65	3,44	-88,93	237,46	23,53	28°07'
Z-140x2,5	140	66	76	2,5	21	15	70,86	73,36	7,43	5,83	233,46	32,95	5,60	86,31	11,77	3,41	-108,65	291,10	28,67	27°57'
*Z-150x2	150	66	76	2	21	15	75,96	73,60	6,18	4,85	222,16	29,25	5,99	70,86	9,63	3,39	-95,45	268,93	24,80	25°48'
*Z-150x2,5	150	66	76	2,5	21	15	75,89	73,40	7,68	6,03	273,86	36,09	5,97	86,31	11,76	3,35	-116,91	329,96	30,21	25°38'
*Z-160x2	160	66	76	2	21	15	80,95	73,68	6,39	5,02	258,50	31,93	6,36	71,06	9,64	3,33	-102,42	303,61	25,96	23°46'
Z-160x2,5	160	66	76	2,5	21	15	80,92	73,44	7,93	6,22	318,10	39,31	6,33	86,32	11,75	3,30	-125,18	372,80	31,62	23°36'
Z-180x2	180	66	76	2	21	15	91,02	73,76	6,79	5,33	339,85	37,34	7,07	71,07	9,64	3,23	-115,91	382,93	27,99	20°23'
Z-180x2,5	180	66	76	2,5	21	15	90,99	73,52	8,43	6,62	418,61	46,01	7,05	86,33	11,74	3,20	-141,71	470,83	34,10	20°14'
Z-180x3	180	66	76	3	21	15	90,96	73,28	10,05	7,88	494,95	54,42	7,02	100,64	13,73	3,17	-166,29	555,72	39,88	20°04'
*Z-200x2	200	66	76	2	21	15	101,07	73,83	7,19	5,65	434,78	43,02	7,77	71,08	9,63	3,14	-129,40	476,12	29,74	17°43'
*Z-200x2,5	200	66	76	2,5	21	15	101,04	73,59	8,93	7,01	535,97	53,04	7,75	86,34	11,73	3,11	-158,24	586,08	36,23	17°34'
Z-200x3	200	66	76	3	21	15	101,01	73,35	10,64	8,35	634,24	62,79	7,72	100,66	13,72	3,08	-185,74	692,53	42,37	17°25'
*Z-225x2,5	225	66	76	2,5	21	15	113,61	73,66	9,56	7,50	707,92	62,31	8,61	86,35	11,72	3,01	-178,91	755,74	38,53	14°58'
Z-225x3	225	66	76	3	21	15	113,58	73,42	11,39	8,94	838,43	73,82	8,58	100,67	13,71	2,97	-210,05	894,04	45,06	14°50'
Z-225x4	225	66	76	4	21	15	113,52	72,94	15,00	11,77	1.088,67	95,90	8,52	126,60	17,36	2,90	-267,91	1.158,30	57,03	14°33'
Z-250x2,5	250	66	76	2,5	21	15	126,16	73,73	10,18	7,99	909,73	72,11	9,45	86,36	11,71	2,91	-199,57	955,56	40,54	12°56'
Z-250x3	250	66	76	3	21	15	126,14	73,49	12,14	9,53	1.078,22	85,48	9,42	100,69	13,70	2,88	-234,36	1.131,50	47,41	12°48'
Z-250x4	250	66	76	4	21	15	126,08	73,00	16,00	12,56	1.402,11	111,20	9,36	126,63	17,35	2,81	-299,03	1.468,70	60,00	12°34'
Z-300x2,5	300	66	76	2,5	21	15	151,25	73,84	11,43	8,97	1.410,76	93,27	11,11	86,38	11,70	2,75	-240,91	1.453,20	43,92	10°
*Z-300x3	300	66	76	3	21	15	151,23	73,60	13,65	10,71	1.674,03	110,70	11,08	100,71	13,68	2,72	-282,98	1.723,40	51,36	9°53'
Z-300x4	300	66	76	4	21	15	151,19	73,12	18,00	14,13	2.182,10	144,33	11,01	126,67	17,32	2,65	-361,28	2.243,8	65,02	9°41'

(\*) Correas con bandas en existencia permanente. (Aceralia Transformados S.A.)